

Description

The JSL-I4V indoor monitor features a slim and elegant design with a 4.3-inch color TFT display and capacitive touch keys for easy operation. It supports high-quality video talk-back, remote unlocking, door-station monitoring, and multiple smart home integrations. With a variety of functions including recording, messaging, alarm input, and app connectivity, the I4V enhances both security and convenience in residential and commercial environments.



Main Features

- 4.3-inch Color TFT Display with sharp IP image (1024×600 resolution)
- Capacitive Touch Keys for easy configuration and operation
- Video Talk-Back & Remote Unlocking for enhanced security
- Supports up to 2 Indoor Monitors per apartment
- High-Quality Audio with adjustable ring and speech volume
- Self-ignition viewing & door opening
- Message & photo storage for visitors
- Guest recording with date list
- Mute mode with visual indication
- Multiple ringtone melodies
- Time & clock display in standby
- Additional IP camera support
- Elevator call function
- Guard call option
- App integration for remote control
- Wide Operating Range: -40°C to 50°C, suitable for various environments
- Multiple Mounting Options: Flush or surface mounting
- Durable ABS Construction in elegant white color

Specification

| | |
|----------------------------|---------------------------------------------------|
| System | Linux |
| Material | ABS |
| Color | White |
| Display | 4.3-inch TFT LCD |
| Resolution | 480×272 |
| Operation | Capacitive Pushbutton |
| Speaker | 8Ω, 1.5W/2W |
| Microphone | -56dB |
| Alarm Input | 4 Alarm Inputs |
| Power Supply | DC24V (SPoE), DC48V (PoE) |
| Working Temperature | -40°C to 50°C |
| Storage Temperature | -40°C to 60°C |
| Working Humidity | 10 to 90% RH |
| IP Level | IP30 |
| Interface | Power In, RJ45 Port, Alarm In Port, Doorbell Port |
| Installation | Flush Mounting / Surface Mounting |
| Dimensions | 184×128 mm |

Dimension



Accessory

JSL-I4V Bracket



JSL-I4V Accessory Bag

